

Switches & Control Gear

Standard Illuminated With Snap-action Switch Element

Detailed product specifications are available on: us.100y.com.tw

01P-RM40.Q1P



01P-RM40.Q1P+B+D12



01P-RM40.Q1P+G+D12



01P-RM40.Q1P+G

01P-RM40.Q1P+O+D24
01P-RM40.Q1P+Y+D12


CHARACTERISTIC:

- Installed hole 16m/m. Available in three sizes appearance:
Square 18*18mm
Circle 18m/m
- Rectangular 18*24 mm
- Offer built-in standard type, to avoid infiltration of liquids before the panel.
- Heightening borders to prevent unnecessary mistakenly touch actuator.
- The use of micro-structure T13 / 4 Baizhi lights, and LED lights Helium Neon Glow Indicator Lamp.
- A fast switching agencies, contact can automatically remove carbon deposition.
- Each switch modules with a set of normally closed and a group of normally open contact.
- Use plastic fire rating UL94V0. Plastic body could extinct by itself


Color: ○ ● ● ● ● ●

SPECIFICATIONS

- Contact material: Silver plated platinum
- Contact capacity: 250 VAC/5A (p. f. =0. 9)
- Electrical conductivity cell life:
5A/250 VAC 50, 000
4A/250 VAC 60, 000
2A/250 VAC 200, 000
1A/250 VAC 400, 000
- Max insulated voltage: In all terminals and some plastic shell, 4000VAC, 50HZ, 1 minute
- Insulated resistance: <500 VDC , >10⁴MΩ
- Resistance welding temperature: 200°C/5sec
- Shell material: High temperature oil resistance performance plastic materials, extinct by itself
- Operating temp: -25°C to +55°C,
- Storage temp: -40°C to +85°C
- Installed hole: Φ16mm



Part No.	Product No.	Manufacturer	Description	Installed Aperture	Contact Function	Contact Rating	Button/Body Color	Lamp (V)
18013	01P-RM40.Q1P	META	Rectangular Momentary Button Switches	φ 16mm	1A1B	250VAC/5A		48V
12762	01P-RM40.Q1P+B+D12	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1A1B	5A/250V	Blue	14Vdc
42918	01P-RM40.Q1P+G+D12	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1A1B	250VAC/5A		12V
44898	01P-RM40.Q1P+O+D24	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1A1B	250VAC/5A	ORANGE	24V
42914	01P-RM40.Q1P+R+D12	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1A1B	12VDC		250VAC/5A
42916	01P-RM40.Q1P+Y+D12	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1A1B	250VAC/5A		12V
50010	01P-RM40.Q1P+G	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1A1B	250VAC/5A		12V




Contact type	1Pole=1A1B; 2Poles=2A2B
Actuating itinerary	3mm
Road to power	1Pole about120gw; 2plose about 250gw
Mechanical life	Reverted1*10 ⁶ ; Alternating1*10 ⁶
Weight	Welding 1P about 7gw; Welding 2P about 8gw



Part No.	Product No.	Manufacturer	Description	Installed Aperture	Contact Function	Contact Rating
29161	01P-RM40.S2P	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	2A2B	5A/250V
39351	01P-RM40.S2P	META	Rectangular Momentary Button Sitches With Lamp	φ 16mm	1 A1B	250VAC/5A



Contact type	1Pole=1A1B; 2Poles=2A2B
Actuating itinerary	3mm
Road to power	1Pole about120gw; 2plose about 250gw
Mechanical life	Reverted1*10 ⁶ ; Alternating1*10 ⁶
Weight	Welding 1P about 7gw; Welding 2P about 8gw



Part No.	Product No.	Manufacturer	Description	Installed Aperture	Contact Rating	Button/Body Color	Lamp (V)
21770	01P-SA65.S1P+R+D12	META	Rectangular Alternative Button Sitches With Lamp	φ 16mm	250VAC/5A	Red/Black	D14V
21771	01P-SA65.S1P+Y+D12	META	Alternative Button Switches	φ 16mm	250VAC/5A	Yellow/Black	D14V



Weight	Welding about 5gw Interpolation about 7. 8gw
Safety norms	
Lamp power	Input voltage
Tungsten Lamp	DC06, DC12, DC24V
Helium Neon Glow Indicator Lamp	AC110, AC220V
LED Lamp	AC/DC: 6, 12, 24V



Part No.	Product No.	Manufacturer	Description	Installed Aperture	Contact Rating	Lamp (V)
32377	01P-SI40.Q	META	Rectangular Momentary Button Sitches With Lamp	φ 16m/m	5A/250VAC	48V/0.8W



T E L : Taiwan: 886-3-5753170
F A X : Taiwan: 886-3-5753172
E-mail: Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
Shenzhen: 86-755-83640655
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
Shanghai: 86-21-64605107
Shanghai: 100y-1@163.com