

# Switches & Control Gear

## Standard Illuminated With Snap-action Switch Element

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)

Part No.	Product No.	Manufacturer	Description	Installed Aperture	Contact Function	Contact Rating	Button/Body Color
44072	T3ISR-1C	TEND	30Knob Operator 1a1b	30mm	1a1b	6A250VAC	black
44061	T3ITL2-1C	TEND	30 Twin-Touch Rectangular Botton	30mm	1a1b	220V	red green
43972	T3KLR-1C	TEND	30Long head ? Round1a1b	30mm	1a1b	6A250V AC	black
43977	T3KMR-1C	TEND	30Mushroom head ound1a1b	30mm	1a1b	6A250V AC	black
43964	T3KSR	TEND	30Key operator Round1a1b	30mm	1a1b	6A250V AC	Black
43961	T3SHR-1C	TEND	30Lever operator Round1a1b	30mm	1a1b	A250V AC	Black
43958	T3SSE-1C	TEND	30Knob operator Round1a1b	30mm	1a1b	6A250V AC	Black
43997	T3TAR2G-1C	TEND	30 Long Head(Alternate) Round Push Botton Switch	30mm	1a1b	220/5VAC	Green
44009	T3TBR2R-1C	TEND	30 Mushroom Head(Alternate) Round Push Botton Switch	30	1a1b	220/5VAC	red
43984	T3TFR2G-1C	TEND	30 Flat Head Round Push Botton Switch	30mm	1a1b	220/5V	Green
44042	T3THR-1C	TEND	30Lever oprator Round1a1b	30mm	1a1b	6A250V AC	red
44015	T3TKR2R-1C	TEND	30 Push-Lock Botton Switch	30mm	1a1b	220/5VAC	red
43992	T3TLR-1C	TEND	30 Long Head Round Push Botton Switch	30mm	1a1b	220/5V	Green
44002	T3TMR2R-1C	TEND	30 Mushroom Head Round Push Botton Switch	30	1a1b	220/5V	red
44040	T3TSR-1C	TEND	30Knob operator Round1a1b	22mm/25mm	1a1b	6A250V AC	red
44021	T3TTL2-1C	TEND	30 Twin-Touch Push Botton	30mm	1a1b	220/5V	red green



TIBN-302-G



TIBR-252

- Dielectric strength: AC2200V for duration of one minute.
- Insulation resistance: Over 100Ω@DC500v.
- Temperature rise : At Contacts less than 30degrees.  
At Terminals less than 25degrees.  
(@Ambient temperature of 40°C, and a continuous current of 10amperes)
- Contact resistance: Less than 30mΩ
- Ambient temperature allowble: -20°C~+60°C

Part No.	Product No.	Manufacturer	Description	Installed Aperture	Contact Rating	Button/Body Color
43666	TIB-252-R	TEND	25 Illuminated push button Switch	25	6A 250V AC	Red
43700	TIB-302	TEND	30 Illuminated push button Switch	30	6A 250V AC	White
43684	TIBN-252-R	TEND	25 Illuminated Push Button Switch	25	220V	Red
39179	TIBN-302-G	TEND	30 Illuminated Push Button Switch	30	220V	Green
43707	TIBN-302-W	TEND	30 Illuminated Push Button Switch	30	220V	White
43694	TIBNR-252	TEND	25 Illuminated Push Button Switch With Ring	25	220V	Green
43719	TIBNR-302	TEND	30 Illuminated Push Button Switch With Ring	30	220V	Red
47802	TIBR-252-G	TEND	25 guard ring Illuminatedlalb220v	25m/m-30m/m	6A 250V AC	Green
47803	TIBR-252-O	TEND	25 guard ring Illuminatedlalb220v	25m/m-30m/m	6A 250V AC	Orange
43689	TIBR-252-R	TEND	25 guard ring Illuminatedlalb220v	25m/m-30m/m	6A 250V AC	Red
47804	TIBR-252-W	TEND	25 guard ring Illuminatedlalb220v	25m/m-30m/m	6A 250V AC	White
43711	TIBR-302	TEND	30 With ring lalb-220V	25m/m-30m/m	6A 250V AC	


## Accessories for Standard Illuminated

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- IP65 Protection
- Switch Rating, 3A, 250VAC
- Flush Mounting into 22.5mm, 21x21mm and 21x27mm cut out
- Illumination using midget-grooved T13/4lamps or single chip LED's
- All standard lenses are transparent with translucent diffuser available in different colours
- For keylock switches 135 different keys are available

Part No.	Product No.	Manufacturer	Description
40918	01-907	EAO	Mounting Tool



Description	Color	Size	Weight_grm
Lens, flat, transparent, for film insertions	Green	12. 8*18. 8mm (0. 503*0. 740)	1
Lens, flat, transparent, for film insertions	White	15. 2*21. 2mm (0. 598*0. 834)	1

Part No.	Product No.	Manufacturer	Description	Type	Color	Size(mm)
14088	01-982.5	EAO	Cap	Rectangular	Green	12.8*18.8
23225	01-982.7	EAO	Cap	Rectangular	White	12.8*18.8

