

Timers & Counters

Time Delay Relay

Detailed product specifications are available on: us.100y.com.tw



Model	H5T-4D	
Power supply	90~250VAC 50/60Hz	
Wattage	5VA max.	
Control Output	A	Two limit contact
	B	Limit & Instantaneous
Output Method	Relay 10A	
Control method	Power ON delay	
Timing method	UP or Down selectable	
Repetivity	±0.1% of F. S	

Setting accuracy	±0.05% of F. S
Reset time	0.1S max.
Reset method	Power OFF reset
Insulation strength	100MΩ/500VDC
Dielectric strength	2.5KV/1 min
Circumstance	-20°C~+60°C, 35~85% RH
Life of relay	20x10 ⁶ Times

Part No.	Product No.	Manufacturer	Description	Ctrl time	(V)	Overload A/Vac
30842	H5T-4D	FOTEK	DIGITAL POWER ON DELAY TIMER	S~0.1H	90~250VAC	250Vac/10A



Features

- Width " Automatic Reset " if power interruption the MDUV288 will reset to your delay time.
- All Solid State (No Moving Parts)
Outstanding ong Life performace A vivid dark blue with Easy-toRead white print Timer.
- Made from Fire/Heat retardment P.B.T. Compound case.
- Delay-On 0.1 to 8 Minutes (Adjustable time dial).

Specifications :

Time :

- Adjustable 0.1 - 8 Minutes
- Repeat accuracy : +/- 2% (Under fixed Conditions)
- Recycle Time : 40ms Maximum (After timing)

Voltage :

- Range : 20 - 288VDC
- Frequency : 60HZ / 50HZ

Output :

- Type : Solid State
- Max. Current : 1A Steady State, 10A Inrush at 55oC
- Min. Current : 40mA
- Voltage drop : Typical 205V at 1A current

Protection :

- Internal Varister and RC snubber Transient Protection
- Min 1500Vrms Dielectric Breakdown
- Min 100mΩ Insulation resistance (Test at 500VDC)

Part No.	Product No.	Manufacturer	Description	Ctrl time	(V)	Overload A/Vac
16022	MDUV288	TOWARD	Delay-on Timer	Delay-on 0.1~8Min.	19-288Vdc	1A/205V



Operating voltage	(DC)12,24 (AC)12,24,110,220,240
Operating voltage range	85~110%
Voltage frequency	50/60Hz
Control time	60 sec.
Contact capacity	250VAC /5A Resistive load
Consume power	3VA
Operating environmental temp	-10~+55°C
Operating environmental humidity	MAX 85%RH

Part No.	Product No.	Description	Ctrl time	(V)
13727	SI-48	Time Delay Relay	60 Sec.	24Vdc



Part No.	Product No.	Description	Ctrl time	(V)
28259	ST-48	DIGITAL COUNTER	0~60sec	DC12V
12932	ST-48	Time Delay Relay	0~120 Sec.	12V



Model	H5T-4D	
Power supply	90~250VAC 50/60HZ	
Wattage	5VA max.	
Control Output	A	Two Limit Contact
	B	Limit & Instantaneous
Output Method	Relay 10A	
Control method	Power ON Delay	
Timing method	UP or Down Selectable	

Repetivity	±0.1% of F. S
Setting accuracy	±0.05% of F. S
Reset time	0.1S max.
Reset method	Power OFF Reset
Insulation strength	100MΩ/500VDC
Dielectric strength	2.5KV/1 min
Circumstance	-20°C~+60°C, 35~85%RH
Life of relay	20*10 ⁶ Times

Part No.	Product No.	Manufacturer	Description	Ctrl time	(V)	Overload A/Vac
32089	SY-2D	FOTEK	DIGITAL POWER ON DELAY TIMER	S~0.1H	90~250VAC	250Vac/10A

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.

Taiwan : 886-3-5753170
Shanghai : 021-54151736 Shenzhen : 0755-83298787

Centenary Materials
Waiting for your phone call



T E L : Taiwan : 886-3-5753170
F A X : Taiwan : 886-3-5753172
E-mail : Taiwan : us_sale@100y.com.tw

Shenzhen : 86-755-83298787
Shenzhen : 86-755-83640655
Shenzhen : 100y@163.com

Shanghai : 86-21-54151736
Shanghai : 86-21-64605107
Shanghai : 100y-1@163.com