

Timers & Counters

Timer Switcher

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Description	Ctrl time	(V)	Overload A/Vac
14122	MH-BC-3H-H-A110	Multi-Segment Time Switcher Relay	3H	110VAC	50/60Hz
19456	MH-BE-2H-M-A220	Multi-Segment Time Switcher Relay		220Vac	250VAC/5A
11001	MH-BE-3H-H-A110	Multi-Segment Time Switcher Relay	9.99/99.9/999 Hours	110Vac	250VAC/5A
33678	MH-BE-3H-M-A110	Multi-Segment Time Switcher Relay	9.99/99.9/999 Hours	110Vac	250VAC/5A
50860	MH-BE-3H-M-A220	"OEC" Multi-Range Digital Timer(MH-SERIES)	9.99/99.9/999 M	AC220V 50/60Hz	250Vac/5A
38753	MH-BE-3H-S-A110	Multi-Segment Time Switcher Relay	9.99/99.9/999	110Vac	250VAC/5A



SPECIFICATIONS

Power Supply	90 or 250 VAC 50/60Hz	Control Method	10 mode
Wattage	5VA max.	DC Output	60 mA /12VDC
Memory Method	EEPROM	Delay Timer<t>	0.1~9.9S
Timing Method	UP or Down Selecting	Insulation Strength	100M Ω/ 500 VDC
Time Input	Hi>6V,Lo<2V	Dielectric Strength	2.5KV/ 1min
Reset Input	Hi>6V,Lo<2V	Circumstance	-20°~60,35~85°C%RH
Output Method	Relay, 1c/ 10A	Life	20X10 ⁶ Times
Output Control	N/R Selectable		

Part No.	Product No.	Manufacturer	Description	Ctrl time	(V)	Overload A/Vac
32077	STP-2D	FOTEK	MULTI-FUNCTION DIFITAL TIMER	0.1s~0.1hr	90~250Vac	250Vac/10A
30723	STP-3D	FOTEK	MULTI-FUNCTION DIFITAL TIMER	0.1s~0.1hr	90~250Vac	250Vac/10A



T3Y-2/110V/60S



TH3Y-4

MODEL	H3Y-2	H3Y-4
DIMENSIONS (mm)	28H*21W*55D	
Mounting & socket	Surface	PYF08A PYF14A
Full timing range	SEC: 1, 3, 6, 10, 30, 60	MIN: 3, 6, 10, 30, 60
Rated voltage	AC: 110V, 220V, 50/60HZ	DC: 12V, 24V
Indicator operating	ON-UP Two indicator lamp ON-UP	
Output contact	Time limit 4C Time limit 2C	3A 250V AC (resistive load)
Life	Mechanical Electrical	5, 000, 000 operations 100, 000 operations at rated load
Accuracy	Repeat error Setting error Voltage error Temp. error	Less than ±3% of full scale Less than ±10% of full scale Less than ±2% Less than ±5% at 25°C
Reset time	Less than 0.2sec	
Consumed power	AC: about 3VA DC: about 2W	
Ambient temperature	-10°C~+55°C	
Ambient humidity	45%~85% RH	
Weight	45g	

Part No.	Product No.	Description	Ctrl time	(V)	Overload A/Vac
10970	T3Y-2/110V/60S	Time Switcher Relay	60S	110Vac	240Vac/5A
11612	T3Y-4/110V/60S	Time Switcher Relay	0~60s	110Vac	240Vac/5A
23775	T3Y-4/110V/6M	Time Switcher Relay	0~10M	110Vac	240Vac/5A max
10971	T3Y-4/220V/60S	Time Switcher Relay	0~60 Sec.	220Vac	240Vac/5A
14618	TH3Y-4	Time Switcher Relay	60s	24VDC	220Vac/3A



Operating voltage	DC (V) : 12, 24 AC (V) : 12, 24, 110, 220, 240
Operating voltage range	Rating operating voltage 85~110%
Power Frequency	50/60HZ
Contact capacity	250VAC 5A Resistive load
Reverted to the time	MAX 0.2 sec.
Consume power	2VA
Life	Machinery: 5, 000, 000次 Electric: 100, 000 (Rating capacity)
Operating environmental temp	-10~+50°C
Operating environmental humidity	MAX 85% RH
Weight	220g

Part No.	Product No.	Manufacturer	Description	Ctrl time	(V)	Overload A/Vac
34994	TTDVNB1852032	ANLY	ATDV Timer Switcher	3S/30S/3M/30M	AC110V/220V	250Vac/5A
39869	TTDVNC1852063	ANLY	ATDV Timer Switcher	6S/60S/6M/60M	AC110V/220V	250Vac/5A
23322	TTDVYC1852063	ANLY	ATDV Timer Switcher	6S/60S/6M/60M	AC110V/220V	250Vac/5A

