

Multimeters & Panel Meters

LCR Meters



FEATURES

- Test Frequency:
 - 12Hz~200kHz (LCR-821)
 - 12Hz~100kHz (LCR-819/829)
 - 12Hz~10kHz (LCR-817/827)
 - 100Hz~2kHz (LCR-816/826)
- 0.05~0.1% Measurement Accuracy
- 100 Sets Memory for Save/Recall of Setup State
- R/Q, C/D, C/R, L/Q Test Modes for all Models; Z/∅, L/R for LCR-821 Only
- Absolute Value, ΔValue, and Δ% Measurement Display
- 240 x 128 dot Matrix LCD Display
- Test Condition and Test Result Shown on the Screen Simultaneously
- Interface :RS-232C , Handler

Detailed product specifications are available on: us.100y.com.tw

Part No.	Product No.	Manufacturer	Description	Test frequency	Display color	Weight
51974	LCR-821	GW Instek	High precision LCR Meter	12Hz~200kHz	240*128 dot-matrix C.C.F.L back light LCD	5.5kg/pc

Digital Earth Testers Ground Tester



FEATURES

- Earth resistance and earth voltage measurement
- 3 ranges for earth resistance measurement, 19. 99, 199. 9, 1999Ohm
- 0 to 199. 9V for earth voltage measurement
- 18mm, large size LCD display, easy to read-out
- Data hold
- circuit provides high accuracy, reliability and durability
- Manual power On/Off or auto power off within 2 minutes after power On
- Built-in over input indication
- Durable & portable housing plastic case with the front protective cover
- Complete testing accessories included

Detailed product specifications are available on: us.100y.com.tw

SPECIFICATIONS

Display	18mm(0.7") LCD (Liquid crystal display) .Max. indication 1999
Function	Earth resistance & Earth voltage measurement
Safety standard	IEC 1010
Overload protection	200V AC for 10 seconds across 2 of the 3 terminals for earth resistance measurement 300V AC for 1 minute on earth voltage range
Insulation resistance	More than 5 Meg ohm between the circuit and the housing case when measured with 500DCV
Operating temp	0 to 50°C (32 to 122°F)
Operating humidity	Less than 80% R. H. .

Part No.	Product No.	Manufacturer	Description
38889	ET-3000	LUTRON	EARTH RESISTANCE TESTER



- Operating temp: 0°C~40°C
- Operating humidity: less than 80%RH
- Consume current: about 27mA
- Dimensions: 10. 2" x4. 4" x1. 9" 258mm (L) x110mm (W) x47mm (H)

Part No.	Product No.	Manufacturer	Description
11440	PROVA 5600	PROVA	Earth Ground Resistance(Hook)



- Operating temp: 0°C to 50°C (14°F to 122°F)
- Storage temp: -20°C to 60°C (-4°F to 122°F)
- Operating humidity: less than 85% RH
- Storage humidity: less than 75% RH
- Dimensions/Weight (5637) : 276mm (L) x 100mm(W) x 47mm(H), 10.8" (L) x 3.9"(W) x 1.9"(H)/ 750g/1.65lbs
- Dimensions/Weight (5600,5601) : 257mm (L) x 100mm(W) x 47mm(H), 10.1" (L) x 3.9"(W) x 1.9"(H)/ 640g/1.41lbs

Part No.	Product No.	Manufacturer	Description
48415	PROVA 5601	PROVA	Earth Ground Resistance
48416	PROVA 5637	PROVA	Clamp on Ground Resistance Tester



- Dimensions: 190 (L) x140 (W) x77 (H) mm
- Operating temp & humidity: 0°C to 40°C (32°F to 104°F) ,less than 80%RH
- Storage temp & humidity: -10°C to 60°C (14°F to 140°F) ,less than 70%RH

Part No.	Product No.	Manufacturer	Description
12617	TES-1700	TES	Earth Ground Resistance

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan : 886-3-5753170

Shanghai : 021-54151736 Shenzhen : 0755-83298787

Centenary Materials

Waiting for your phone call



T E L : Taiwan: 886-3-5753170
F A X : Taiwan: 886-3-5753172
E-mail : Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
Shenzhen: 86-755-83640655
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
Shanghai: 86-21-64605107
Shanghai: 100y-1@163.com

58-04