

# Multimeters & Panel Meters

## Digital Clamp-Meters

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### DISPLAY

- Display: 3 1/2 digits LCD with max. reading 1999, plus decimal point, unit symbol indication.
- Overload Indication: LCD will show "1" in the left highest position.
- Low Battery Indication: Replace battery immediately when LCD displays "⎓".

### POWER SUPPLY

- Battery type: 9V NEDA 1604 IEC 6F22 JIS 006P x 1pc.
- Battery life: about 200 hours.

### FUNCTIONS

- TM-22E with True RMS measurements
- Function Keys: Data Hold
- Test Ranges: ACA, ACV, O
- The maximum conductor size is 35mm.

### DIMENSION

- Size : 218x75x43 mm (LxWxH)
- Weight : about 335g (including battery)

Part No.	Product No.	Manufacturer	Description
16241	TM-21E	TENMARS	Digital AC Clamp-on Meter
16239	TM-23E	TENMARS	Digital AC Clamp-On Meter



### DISPLAY

- 3 3/4 digits LCD with max. reading 3999, plus decimal point, unit symbol indication.
- Back Light (TM-27E)
- Overload Indication: LCD will show "OL" in the left highest position.
- Low Battery Indication: Replace battery immediately when LCD displays "⎓".

### POWER SUPPLY

- Battery type: 9V NEDA 1604 IEC 6F22 JIS 006P x 1 pc.
- Battery Life: about 200 hours.

### FUNCTIONS

- TM-27E with True RMS measurements
- Auto range, Auto power Off
- High speed bargraph
- Function Keys: Data Hold, Max/Min Hold
- Range key (TM-26E)
- Key (TM-27E) Backlit Display for easy reading in the dark.
- Test Ranges: ACV, ACA, DCV, DCA, Ω, Frequency, Continuity
- The maximum conductor size is 35mm.

### DIMENSION

- Size : 218x75x43 mm (LxWxH)
- Weight: about 375g. (Including battery)

Part No.	Product No.	Manufacturer	Description
16242	TM-27E	TENMARS	3 3/4 Digital Clamp Meter

## BRYMEN\_ 4000 COUNTS Digital Clamp-Meters

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- Display: 3-3/4 digits 4000 counts LCD display (s)
- Operating temperature: 0°C to 40°C
- Altitude: operating below 2000m
- Storage temperature: -20°C to 60°C, <80% R. H. (with battery removed)
- Power consumption: 2.5mA typical
- Dimension: L190mmxW63mmxH32mm
- Weight: 187 gm approx

Part No.	Product No.	Manufacturer	Description
15716	BM-111	BRYMEN	BRYMEN_ Single/Double Displays Clamp-on Multimeter
15717	BM-112	BRYMEN	BRYMEN_ Single/Double Displays Clamp-on Multimeter
15718	BM-125	BRYMEN	BRYMEN_ Single/Double Displays Clamp-on Multimeter
15719	BM-126	BRYMEN	BRYMEN_ Single/Double Displays Clamp-on Multimeter

## Phase & Continuity Indicators Phase & Continuity Indicators

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



Part No.	Product No.	Manufacturer	Description
48438	61-521	IDEAL	IDEAL_3 Phase Motor Rotation Tester

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.

Taiwan: 886-3-5753170  
Shanghai: 021-54151736 Shenzhen: 0755-83298787

**Centenary Materials**  
Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: [100y-1@163.com](mailto:100y-1@163.com)