

Multimeters & Panel Meters

Pocket Sized Multimeters

Detailed product specifications are available on: us.100y.com.tw



- 3-3/4 digits 3200 count
- Compact size test leads that are directly fixed to the main
- Body provide safety in high voltage measurement
- Test probe can be snapped into a fixed position
- Full auto range
- Arc. Bargraph

Part No.	Product No.	Manufacturer	Description	Range Manual/Auto	Diode Y/N	Frequency(Hz)	Batt. Test Yes/No	Buzzer Yes/No	Auto off Yes/No
10939	PM-10	SANWA	Sanwa_Digits Professional Industrial Multimeter	Auto	Yes	No	No	Yes	No



- Voltage: DC400m/4/40/400/500V AC 4/40/400/500V DC $\pm(1.3\%+3\text{dgt})$ AC $\pm(2.3\%+5\text{dgt})$
- Resistance: 400/4K/40K/400K/4M $\pm(2\%+5\text{dgt})/40M\Omega\pm(10\%+5\text{dgt})$
- Capacitance: 4n/40n/400n/4u $\pm(5\%+10\text{d})$ 40u/200u $\pm(10\%+15\text{dgt})$
- Frequency: 9. 999Hz~99. 9KHz
- DUTY: 0. 1%~99%
- Size: 108Hx56Wx11. 5D/mm

Part No.	Product No.	Manufacturer	Description	Range Manual/Auto	Diode Y/N	Frequency(Hz)	Batt. Test Yes/No	Buzzer Yes/No	Auto off Yes/No
22081	PM-3	SANWA	Sanwa_Digital Multimeter	Auto	Yes	Yes	No	Yes	Yes

Fluke_Multimeters and Accessories Fluke_70 Series Multimeters

Detailed product specifications are available on: us.100y.com.tw



- Display: 3000 counts, 30, 000 counts, 100, 000 counts
- Reading rates: fast (20 times per second) Medium 95 time per second, Slow (2. 5 times per second)
- Size: 216mm W x 93mm H x 286mmD (8. 5" W x 3067" H x 11. 27" D)
- Weight: net 2. 4kg (5. 2lb) ;with battery 3. 2kg (7 lb)

Part No.	Product No.	Manufacturer	Description
2781	FLU45	FLUKE	FLUKE_45 Dual Display Multimeter



FLU73-III

- Voltage, Ohms, 10A and mA current, diode test, continuity beeper
- Digital display with analog bar graph
- All inputs protected to 600V CAT II
- Protected from overvoltage transients to 4kV per IEC 1010-1
- 0. 3% basic accuracy
- Fast autorange and range hold
- Rugged durable removeable holster with Flex-stand™ protects the multimeter
- Lifetime manufacturer warranty
- Includes: Multimeter, Hard-Point™ test leads, Protective holster with Flex-stand™, 9V battery, instructions

Part No.	Product No.	Manufacturer	Description	Base accuracy	Max.Vdc	Max.voltage (ACV)	Base accuracy(ACV)	Max.Amp.(DCA,ACA)	Resolving(DCA,ACA)	Max.transistor (Ω)	Base accuracy(Ω)
7377	FLU73-III	FLUKE	FLUKE_70 Series III Digital Multimeters	0.3%	600V	600V	2%	10A	0.01mA	33M Ω	0.5%



FLU77-IV

General specifications

Maximum voltage between any terminal and earth ground	1000 V
Surge protection	8 kV peak per IEC 61010
Fuse for mA inputs	440 mA, 1000 V FAST Fuse
Fuse for A input	11 A, 1000 V FAST Fuse
Display	Digital: 6,000 counts, updates 4/sec; Bar Graph: 33 segments, updates 32/sec
Altitude	Operating: 2000 m; Storage: 12,000 m
Temperature	Operating: -10 °C to +50 °C; Storage: -40 °C to +60 °C
Temperature coefficient	0.1 X (specified accuracy / °C) (< 18 °C or > 28 °C)
Electromagnetic compatibility (EN 61326-1:1997)	In an RF field of 3 V/M, accuracy = specified accuracy except in temperature: specified accuracy ± 5 °C, ± 9 °F
Relative humidity (maximum non-condensing)	90 % to 35 °C; 75 % to 40 °C; 45 % to 50 °C
Battery life	400 hours typical (Alkaline)

Part No.	Product No.	Manufacturer	Description	Base accuracy	Max.Vdc	Max.voltage (ACV)	Base accuracy(ACV)	Max.Amp.(DCA,ACA)	Resolving(DCA,ACA)	Max.transistor (Ω)	Base accuracy(Ω)
48249	FLU77-IV	FLUKE	FLUKE_70 IV Series Digital Multimeters	0.3%	1000V	1000V	2%	10A	0.01mA	50M Ω	0.5%

