

# Multimeters & Panel Meters

## Fluke\_80 Series Multimeters

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- Compatible with Fluke DMM
- High accuracy, fast reading for low voltage (below 24 V AC, 60 V DC) applications
- Measurement range: -50 to 150°C
- Output: 1 mV/°C or 1 mV/°F (switchable)
- One year warranty

Part No.	Product No.	Manufacturer	Description	Temp °C/°F
28494	80T-150U	FLUKE	FLUKE_80T-150U Universal Temperature Probe(for DMMs)	-50~150



The 180 series are the only choice for users who simply want the best meter available

The two top models 187 and 189, with integrated holsters, are the smartest meters when it comes down to performance, features and more. Extremely fast readings, extended ranges, the highest bandwidth, accuracy and resolution are the basis for their performance. Features like a dual display with bargraph and backlight, true-RMS AC/AC+DC measurements and a PC interface make them suitable for the most demanding applications. In addition, the 189 has a readings memory for up to 100 readings and a unique stand-alone logging function to measure hard to find intermittent problems

Part No.	Product No.	Manufacturer	Description	Max V(DCV)	Counts	Accuracy(DCV)	Max V(ACV)	Accuracy(A CV)	Max.V(DCA)	Accuracy(DCA)	Max.V(ACA)	Accuracy(A CA)	Transistor(Ω)	Accuracy(Ω)	Capacitor	Frequency	Temp °C/°F
12947	FLU 187ECJKT	FLUKE	FLUKE_True-rms Multimeter	1000V	50,000	(0.025%+5)	1000V	(0.4%+40)	10A	(0.15%+2)	10A	(0.75%+5)	500M	(0.05%+2)	0.001nF~50mF	0.5Hz~1000kHz	-200~1350



Part No.	Product No.	Manufacturer	Max V(DCV)	Counts	Accuracy(DCV)	Max V(ACV)	Accuracy(A CV)	Max.V(DCA)	Accuracy(DCA)	Max.V(ACA)	Accuracy(A CA)	Transistor(Ω)	Accuracy(Ω)	Capacitor	Frequency
4147	FLUK-020-136	FLUKE	1000V	4000	(0.5%+3)	1000V	(1%+3)	10A	(1.5%+3)	10A	(1.5%+3)	40M	(0.5%+2)	0.01nF~100uF, (2.0%+5)	100KHZ



The 180 series are the only choice for users who simply want the best meter available

The two top models 187 and 189, with integrated holsters, are the smartest meters when it comes down to performance, features and more. Extremely fast readings, extended ranges, the highest bandwidth, accuracy and resolution are the basis for their performance. Features like a dual display with bargraph and backlight, true-RMS AC/AC+DC measurements and a PC interface make them suitable for the most demanding applications. In addition, the 189 has a readings memory for up to 100 readings and a unique stand-alone logging function to measure hard to find intermittent problems

Part No.	Product No.	Manufacturer	Description	Max V(DCV)	Counts	Accuracy(DCV)	Max V(ACV)	Accuracy(A CV)	Max.V(DCA)	Accuracy(DCA)	Max.V(ACA)	Accuracy(A CA)	Transistor(Ω)	Accuracy(Ω)	Capacitor	Frequency	Temp °C/°F
15642	FLUKE-189	FLUKE	FLUKE_187/189 Digital Multimeters	1000V	50,000?	(0.025%+5)	1000V	(0.4%+40)	10A	(0.15%+2)	10A	(0.75%+5)	500M	(0.05%+2)	0.001nF~50mF	0.5Hz~1000kHz	-200~1350



Part No.	Product No.	Manufacturer	Description	Max V(DCV)	Counts	Accuracy(DCV)	Max V(ACV)	Max.V(DCA)	Max.V(ACA)	Capacitor	Frequency
28738	FLUKE87-5	FLUKE	Fluke_5 Digital Industrial True-rms Multimeter with Temperature	Measure up to 1000 Vdc	4-1/2 digit mode	0.05% dc accuracy	Measure up to 1000 Vac	Measure up to 10A, 20A for up to 30 seconds	Measure up to 10A, 20A for up to 30 seconds	10,000F capacitance range	Frequency to 200 kHz and % duty cycle

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170

Shanghai: 021-54151736 Shenzhen: 0755-83298787

**Centenary Materials**

Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: [100y-1@163.com](mailto:100y-1@163.com)