

Multimeters & Panel Meters

TES_Multimeter Accessories

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Manufacturer	Description
33160	TL-E60	TES	TES-32A
16956	XTES-2804A	TES	RS232
32949	XTES-32B	TES	RS232

PROVA_Series Digit Multimeters

Detailed product specifications are available on: us.100y.com.tw



FEATURES

- 60,000 count and dual input channels
- 0.04% DC basic accuracy and 0.2% AC basic accuracy
- Bandwidth of 10KHz(max)
- Fast ACV, ACA response
- Dual channels measurement similar to a dual channels DSO (V+V, V+A)
- Hz + duty cycle dual display
- Capacitance measurement
- Standalone data logging of 10,708 records for both channels(803)
- RS-232C interface
- Application Software (Option)
- 1/7 the cost

General Specification

Battery Type:	9V
Display:	5 + 5 digits LCD with 30 segments bar graph
Range Selection:	auto and manual
Overload Indication:	OL
Power Consumption:	4 mA (approx)
Operating Temperature:	-10 °C to 50 °C
Operating Humidity:	less than 85% relative
Altitude:	up to 2000M
Storage Temperature:	-20 °C to 60 °C
Storage Humidity:	less than 75% relative
Dimension:	207mm(L) x 101mm (W) x 47mm (H) 8.15" (L) x 4" (W) x 1.85" (H)
Weight:	430g / 15.2oz (battery included)
Accessories:	Users manual x 1 9V battery x 1 801A1:Holster 801A2:RS-232C interface cable + software

Part No.	Product No.	Manufacturer	Description
38783	PROVA 803	PROVA	PROVA_Digital Multi-Meter



FEATURES

- 0.02% DC and 0.1% AC basic accuracy
- 60,000 counts resolution
- 200KHz (max.) bandwidth
- True RMS with fast ACV/ACA response
- Dual channels measurement similar to a dual channels DSO (V+V, V+A)
- RS-232C ASCII interface
- Data logging (model 903 with 10,708 records for both channels)
- Capacitance measurement
- Free software (901,903)
- 1/3 the cost

General Specification

Battery Type	9V
Display	5 + 5 digits LCD with 30 segments bar graph
Range Selection	auto and manual
Overload Indication	OL
Power Consumption	6 mA (approx)
Operating Temperature	-10 C to 50 C
Operating Humidity	less than 85% relative
Altitude	up to 2000M
Storage Temperature	-20 C to 60 C
Storage Humidity	less than 75% relative
Dimension	207mm(L) x 101mm (W) x 47mm (H) 8.15" (L) x 4" (W) x 1.85" (H)
Weight	430g / 15.2oz (battery included)
Accessories	Users manual x 1 9V battery x 1 RS-232C interface cable

Part No.	Product No.	Manufacturer	Description
40834	PROVA-901	PROVA	Digital Multi-Meter
17972	PROVA903	PROVA	Digital Multi-Meter

YF_Multimeters and Accessories

Detailed product specifications are available on: us.100y.com.tw

YF_Series Digital Multimeter



DISPLAY

- 3 1/2 digits LCD max. reading 2000
- with maximum reading 2000 counts
- Automatic polarity indication
- The "—" appears when the battery

DIMENSION

- Size: 128x72x36mm (LxWxH)
- Weight: about 140g

ACCESSORIES

- User's manual
- Test leads
- 9V battery x 1pc

POWER SUPPLY

- Battery type: 9V NEDA 1604 IEC 6F22
- JIS 006P battery x 1pc.
- Battery life: about 100 hours

Part No.	Product No.	Manufacturer	Description	Range Manual/Auto	Tr.(hFE)	Diode Y/N	Frequency(Hz)	Capacitance	Auto off Y/N	Batt. Test Y/N	Buzzer Y/N	Temp. Y/N
39562	YF-1000	YFE	3 1/2 Digital Multimeter	Manual	0~1000	Yes	No	No	No	Yes	Yes	No

