

# Multimeters & Panel Meters

## DM\_Series Digital Multimeter

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



- Voltage: DC200m/2/20/200/1000V AC200m/2/20/200/750V DC±(0.5%+1dgt) AC±(1.2%+3dgt)
- Current: 200u/2m/20m/200m/10A DC±(1%+1dgt) AC±(1.5%+3dgt)
- Resistance: 200/2K/20K/200K/2MO ±(1%+2dgt)/20MO ±(2%+4dgt)
- Capacitance: 2n/20n/200n/2u/20uF ±(3%+10dgt)

Part No.	Product No.	Description
29262	DM-1230	3 1/2 Digital Multimeter



- Voltage: DC200m/2/20/200/1000V AC200m/2/20/200/750V DC±(0.5%+1dgt) AC±(1.2%+3dgt)
- Current: 200u/2m/20m/200m/10A DC±(1%+1dgt) AC±(1.5%+3dgt)
- Resistance: 200/2K/20K/200K/2MO ±(1%+2dgt)/20MO ±(2%+4dgt)
- Capacitance: 2n/20n/200n/2u/20uF ±(3%+10dgt)
- Frequency: 1Hz~20MHz ±(0.5%+2dgt)
- Dimensions: 153H×74W×45D/mm

Part No.	Product No.	Description
29263	DM-1240	3 1/2 Digital Multimeter



- Temperature: -50°C~1370°C ± 1.8%
- Capacitance: 0~2n/20n/200n/2u/20uF ±3%
- Frequency: 1Hz~20MHz±0.5%
- DCV: 0~200m/2/20/200/1000V±0.8%
- ACV: 0~200m/2/20/200±1.2%/750V±1.5%
- DC/ACA: 0~200u/2m/20m/200m±1%/10A
- Ω: 0~200/2K/20K/200K/2M±1%/20M±2%

Part No.	Product No.	Description	Capacitance
23831	DM-1250	3 1/2 Digital Multimeter	YES



- Voltage: DC200m/2/20/200/1000V, AC200m/2/20/200/700V DC±(0.5%+3d)/AC±(0.8%+5d)
- Current: AC/DC2m/20m/200m/20A DC±(0.8%+3d)/AC±(1%+5d)
- Resistance: 200/2K/20K/200K/2M/20M/200MO ±(0.8%+3dgt)
- Capacitance: 2n/20n/200n/2u/200uF ±(2.5%+20dgt)
- Dimensions: 190H×88.5W×27.5D/mm

Part No.	Product No.	Description
29264	DM-2610	3 1/2 Digital Multimeter



- Voltage: DC200m/2/20/200/1000V AC200m/2/20/200/700V DC±(0.5%+3d)/AC±(1%+4d)
- Current: AC/DC2m/20m/200m/20A DC±(0.8%+4d)/AC±(0.8%+5d)
- Resistance: 200/2K/20K/200K/2M/20M/200MΩ ±(0.8%+3dgt)
- Capacitance: 20n/200n/2u//20u/200uF ±2.5%
- Inductance: 2m/20m/200m//2/20h ±2.5%
- Temperature: -40°C~1000°C±(0.8%+4dgt)
- Frequency: 1Hz~10MHz±(0.8%+3dgt)

Part No.	Product No.	Description
29265	DM-2630	3 1/2 Digital Multimeter



- Voltage: DC200m/2/20/200/1000V AC2/20/200/700V DC±(0.1%+5d)/AC±(0.8%+25d)
- Current: AC/DC2m/20m/200m/20A, DC±(0.5%+4d)/AC±(1.5%+25d)
- Resistance: 200/2K/20K/200K/2M/20M ±(0.4%+5dgt)
- Capacitance: 2n/20n/200n/2u/200uF ±3.5%
- Frequency: 1Hz~200KHz±(1.5%+25dgt)
- Conductivity: 0.1nS~100nS ±(1%+30dgt)
- Dimensions: 190H×88.5W×27.5D/mm

Part No.	Product No.	Description
29266	DM-2650	3 1/2 Digital Multimeter

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170  
Shanghai: 021-54151736 Shenzhen: 0755-83298787

**Centenary Materials**  
Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: [100y-1@163.com](mailto:100y-1@163.com)