

Multimeters & Panel Meters

Multi-Meter Test Probes

Detailed product specifications are available on: us.100y.com.tw



- One pair (red, black) of nickel plated pincers 5mm
- 11.4 cm flexible insulated shaft
- Recommended for use with TL222 and and TL224 leads
- CAT IV 600V, CAT III 1000V, 1A rating. UL li
- One year warranty

Part No.	Product No.	Manufacturer	Description
28437	AC283	FLUKE	FLUKE_Pincer Clips



C-AU



C-CD



C-CP

Part No.	Product No.	Manufacturer	Description
11863	C-AU	SANWA	SAMWA_Bag
11862	C-CD	SANWA	SAMWA_BOX PC100/CD100
11864	C-CP		BOX CP-7D



FC-07



FC-10



FC-15A



FC-15B

Part No.	Product No.	Description
2901	FC-07	Multimeter Test Probe
3291	FC-10	Multimeter Test Probe
3292	FC-15A	Multimeter Test Probe
6288	FC-15B	Multimeter Test Probe



Part No.	Product No.	Manufacturer	Description
33208	GTL-108	GW Instek	GOM-802 Test Probe



HVP-40

SPECIFICATIONS

Input resistance	Approx. 1000MΩ	Ground lead length	90cm (3ft)
Max. operating voltage	DC: 0~40KV AC: 1~28KV (50/60Hz)	Output cable length	100cm (3.3ft)
Polarity	Positive/Negative	For	DMM
Accuracy	DC: ±1% to 20KV, ±2% to 40KV AC: -50% to -10% (1~28KV; 50/60Hz)	Output division	1V/1KV
Temperature coefficient	≤200PPM/°C	Dimensions	340mmx80Φ
Maximum Loading current	≤40μA (at 40KV DC)	Weight	about 300g
Maximum loading power	≤1.6watt	Remark	For 10MΩ input impedance DMM (Accuracy<0.5%) only
Operating temperature	0~+50°C		
Storage temperature	-20~+70°C		

Part No.	Product No.	Description
12119	HVP-40	PINTEK_Multimeter Test Probe
30165	HVP-40DM	DC HIGH VOLTAGE DC40KV PROBE METER



KT-001



KT-002



KT-003



KT-004



KT-005



KT-006



KT-008



KT-009



KT-010



KT-011



KT-012

Part No.	Product No.	Description
48728	KT-001	Multimeter Test Probe
48729	KT-002	Multimeter Test Probe

