

Multimeters & Panel Meters

3 1/2 Digit Voltage , Ampere Meter

Detailed product specifications are available on: us.100y.com.tw



- Accuracy: $\leq 0.025\% \pm 1$ digit
- Input resistance: ≥ 1.0 Mega ohm
- Input power: DC+4.75~+5.25V/120mA
- Consume power: ≤ 0.6 W
- Operating temp: 0~50°C
- Operating humidity: 0~85%

Part No.	Product No.	Description	L*W*D(mm)	Measure range	Vin
39923	C113BMOE	3-1/2 Digital Panel Meter	40*72*35mm	DC0.001~1.999V	DC5V/150mA



CHY-700X



CHY-701X

Part No.	Product No.	Manufacturer	Description	L*W*D(mm)
48205	CHY-700X	Chy	3 1/2 LCD Digital Panel Meter	36*24*25.4
48206	CHY-701X	Chy	3 1/2 LCD Digital Panel Meter	36*24*25.4



General specifications

- Display: 3 1/2 digit liquid crystal display (LCD) with maximum reading of 1999
- Measurement rate: 2.5 times per second, nominal,
- Current consumption 50mA max.
- Measurement type: Half-wave average rms calibrated for sinusoidal input
- Operating environment: 0°C to 60°C (32°F to 140°F)
- Storage temperature: -20°C to 75°C (-4°F to 167°F)
- Humidity: less than 75% RH.

Part No.	Product No.	Manufacturer	Description	L*W*D(mm)
48183	CHY-710ACV	Chy	3 1/2 LCD Digital Panel Meter	36*24*25.4
48184	CHY-710DCV	Chy	3 1/2 LCD Digital Panel Meter	36*24*25.4



Part No.	Product No.	Manufacturer	Description	L*W*D(mm)
48203	CHY-711ACV	Chy	3 1/2 LED Digital Panel Meter	36*24*25.4
48204	CHY-711DCV	Chy	3 1/2 LED Digital Panel Meter	36*24*25.4



SPECIFICATIONS

- Display: 3 1/2 digit liquid crystal display (LCD) with maximum reading of 1999
- Measurement rate: 2.5 times per second, nominal
- Operating environment: 0°C to 60°C (32°F to 140°F)
- Storage temperature: -20°C to 75°C (-4°F to 167°F)
- Humidity: less than 75% RH
- 12LED (LCD negativered backlit)

Part No.	Product No.	Manufacturer	Description	L*W*D(mm)
48182	CHY-740X-A	Chy	3 1/2 LCD Digital Panel Meter	72*36*16.25
42894	CHY-740X-V	Chy	3 1/2 LCD Digital Panel Meter	72*36*16.25
48192	CHY-741X-A	Chy	3 1/2 LED Digital Panel Meter	72*36*16.25
48191	CHY-741X-V	Chy	3 1/2 LED Digital Panel Meter	72*36*16.25



Part No.	Product No.	Description	L*W*D(mm)	Measure range	Resolution (max)	Vin	Win
48585	CSM-321AN-5-A	AC Digital Panel Meter		0~300Vac		AC115/230V	
18093	CSM-321AN-6-A	3 1/2 Digit Voltage Meter	96*48*117	0~600Vac	1V	AC115/230V	1.5*rated for 10 second
48986	CSM-321AN-F-A	AC current first-Table				220V	5A
48145	CSM-321AN-G-A	AC current number Head		0~10A		AC115/230V	
42436	CSM-321DN-3-A	3 1/2 Digit Voltage Meter	96*48*117	0~19.99Vdc		AC115/230V	
15303	CSM-321DN-6-A	3 1/2 Digit Voltage Meter	96*48*117	0~600Vdc	1V	AC115/230V	1.5*rated for 10 seconds
42433	CSM-321DN-B-A	3 1/2 Digit Voltage Meter	96*48*117	0~1.999mA		AC115/230V	
16149	CSM-321DN-C-A	3 1/2 Digit Ampere Meter	96*48*117	0~19.99mA/DC	0.01mA/DC	AC115/230V	10*rated for 10 seconds



FEATURE

- Measuring process signal mA, Vdc, Potentiometer, Pulse/u.
- Accuracy: $\pm 0.1\%$
- 3 1/2 Digital display: 1999
- Easy-to-wire, screw type terminal
- Outside dimensions is 1/8 DIN standard (96x48 mm)
- High stability & low cost

Part No.	Product No.	Description	L*W*D(mm)	Measure range	Resolution (max)	Vin	Win
42083	CSR-321-A4-N-D24	3 1/2 DC Current digital Head	96*48*118	4~19.99mVdc	0.1mA	24V	20mA
16373	CSR-321-A4-N-A	3 1/2 Digit Ampere Meter	96*48*118	4~19.99mVdc	0.1mA	AC115/230V	10*rated for 10 seconds

