

Multimeters & Panel Meters

4 1/2 Digit Voltage , Ampere Meter

Detailed product specifications are available on: us.100y.com.tw



FEATURE

- Measuring DCA, DCV, ACA, ACV, Hz
- Accuracy: DC: $\pm 0.04\%$, AC: $\pm 0.1\%$
- 4 1/2 Digital display: 19999
- Easy-to-wire, screw type terminal
- Outside dimensions is 1/8 DIN standard (96x48mm)
- High stability & low cost

Part No.	Product No.	Description	L*W*D(mm)	Measure range	Vin	Resolution (max)	Win
16326	CSM-421D-4-A	4 1/2 Digital Panel Meter	96*48*117	0~199.99Vdc	AC115/230V	0.01V	10*rated for 10 seconds
43515	CSM-421D-4-D12	4 1/2 Digital Panel Meter	96*48*117	0~19.99Vdc	0.01V	DC12V	10*rated for 10 seconds
21152	CSM-421D-7-A	4 1/2 Digital Panel Meter					
16630	CSM-421D-D-A	4 1/2 Digital Panel Meter	96*48*117	0~199.99mAdc	AC115/230V	0.01mA	10*rated for 10 seconds
16328	CSM-421D-E-A	4 1/2 Digital Panel Meter	96*48*117	0~1.999Adc	AC115/230V	0.01V	10*rated for 10 seconds
16629	CSM-421D-V0-A	4 1/2 Digital Panel Meter	96*48*117	0~50.00Vdc	AC115/230V		10*rated for 10 seconds



Part No.	Product No.	Description	L*W*D(mm)	Measure range	Vin	Resolution (max)	Win
39934	CSS-40D-A4-HD-N-N-A	Digital panel meter	120*93*45	0-1V	2.0mV	100mA	100mA/1V



FEATURES

- Relay Output Delay 0~9sec.
- 4 - sets HH, HI, LO, LL (DE-S944)
- 2 - sets HI, LO (DE-S942)
- True RMS V/A
- CT or PT Rate Free Setting
- Direct Setting Function
- DIN Case 96 x48mm

SPECIFICATIONS

Max. Display	4 digits (9999)
Polarity Display	"-" symbol is displayed automatically
Over Range Indication	" 0L "
Conversion Rate	2.5/sec. (DC) or 1/sec. (AC)
Decimal Point	Settable to any digit position by front sheet switch
External Control	Hold
Accuracy (23± 5°C)	$\pm 0.1\%$ F.S. ± 2 digits
Operating Temp. / Humidity	0~50°C / Below 80% R.H. (No Condensation)
Storage Temp. / Humidity	-10~60°C / Below 70% R.H. (No Condensation)
Power Supply	AC 115/230V $\pm 10\%$, 50/60Hz DC 12, 24, 48, 120V $\pm 20\%$
Power Consumption	Approx. 5VA
Weight	Approx. 420g

Part No.	Product No.	Manufacturer	Description	L*W*D(mm)	Vin	Resolution (max)	Win
28540	DE-S942A-A6		Digital panel meter _ -9999 ~ +9999	142*95*47mm	AC 115/230V 10%, 50/60Hz	-9999 ~ +9999	AC 115/230V 10%
28408	DE-S942D-A6	DEREE	Digital panel meter _ -9999 ~ +9999	142*95*47mm	AC 115/230V 10%, 50/60Hz	-9999 ~ +9999	AC 115/230V 10%

5 Digit Voltage , Ampere Meter

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Description	L*W*D(mm)	Measure range	Vin
38714	G315BP0E	24*48 Digit Frequency Meter	48*24*48mm	0.100Hz~9961.4KHz	5VDC



SPECIFICATION

Electrical Characteristics	Conforming to EIA RS-485
Communication Method	2-wires system half-duplex
Transmission Speed	2400/4800/9600/19200pbs
DC Output	Isolation 12 bit D/A
Sampling time	Abt. 0.8 sec. Typically
Frequency range	45~400Hz for AC range
Over indication	Flash " OFL " or " -OFL "
Over Input Signal	Flash display
Aux power source	AC 110/220V10%, 50/60Hz
Power consumption	for two setting (S2-412PA-2) \leq AC 4VA for four setting(S2-412PA-4) \leq AC 5VA
Operating temperature range	0~60°C
Storage temperature range	-10~70°C

FEATURES

- Programmable display ± 19999
- Accuracy: $\pm 0.05\%$ to $\pm 0.2\%$
- Auto-zero and hold function.
- Max. four setting and contact points
- Outside dimension is DIN standard(96x48mm)

Part No.	Product No.	Description	L*W*D(mm)	Measure range	Vin	Win
19382	S2-412PA-2	48*96 Digital Panel Meter	48*96*154	0.01~100.00A/AC	AC110V/AC220V	8.0A/AC

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170

Shanghai: 021-54151736 Shenzhen: 0755-83298787

Centenary Materials

Waiting for your phone call



T E L : Taiwan: 886-3-5753170
F A X : Taiwan: 886-3-5753172
E-mail: Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
Shenzhen: 86-755-83640655
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
Shanghai: 86-21-64605107
Shanghai: 100y-1@163.com