

Adhesives & Cleaning & Service AIDS

Surface Mount Paste



Detailed product specifications are available on: us.100y.com.tw

Part No.	Product No.	Manufacturer	Description	Capacity
9877	Instant Adhesive	BISON	Instant Adhesive	24ml

Expanding filler Foam



Detailed product specifications are available on: us.100y.com.tw

Part No.	Product No.	Manufacturer	Description	Capacity
2522	DP250	Panrico	PU (Polyurethane) doming resin	250gm
48697	PU500	Panrico	PU (Polyurethane) doming resin	500gm

General Purpose Silicone Sealants Silicone

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Capacity	Application
13382	BB300G	300g	Heat conductive



Shin-Etsu Silicone KE-40RTV is a non-flowing, one component RTV silicone rubber compound. When extruded from collapsible tubes, or cartridge, it reacts with the moisture in the air and will cure into a resilient elastomer at room temperature. KE-40RTV is self-extinguishing type, and meets UL-94, V-0. The cured rubber of KE-45RTV has excellent resistance to heat, cold, weather, and excellent dielectric properties.



Part No.	Product No.	Manufacturer	Description	Capacity	Application
5613	KE-40RTV	ShinEtsu	ShinEtsu_Silicone (White, Liquid)	150g	Heat conductive, Waterproof and insulation.
14616	KE40W-B	ShinEtsu	Shin-Etsu_Silicone (Black, Liquid)	500g	Heatproof Cold-resistance ? Shock-resistance, Tolerance



Part No.	Product No.	Manufacturer	Description	Capacity	Application
14739	KE4560G	ShinEtsu	Shin-Etsu_Heat Skin Compound	150g(330ml)	Heat conductive, Waterproof and insulation.
12472	KE45T-M	ShinEtsu	Shin-Etsu_Silicone (Liquid)	100g	



Part No.	Product No.	Description	Capacity
23490	LDC-737	DOW CORNING 737 NEUTRAL CURE SEALANT	100ml



Part No.	Product No.	Description	Capacity	Application
10766	SE9168	Silicone (Gray)	130g/Stick	Heat conductive



Part No.	Product No.	Description	Capacity	Application
22115	SE9168-B	Silicone (Gray)	330ml/Stick	Heat conductive



Field of application

For the safe removal of residues of cured silicon sealant in joints or on surfaces. Can be used on ceramic tiles, glass, metals, plastic, laminates, aluminium and enamel. Not suitable for nylon. Staining possible on porous materials and painted wood.

Properties

- Dilutability: do not dilute.
- Temp. resistance: not applicable.
- Age resistance: good.

Part No.	Product No.	Manufacturer	Description
9873	Silicone	BISON	Silicone Sealant Glass

