

Adhesives & Cleaning & Service AIDS

High Temp. Tapes

Detailed product specifications are available on: us.100y.com.tw



- Material : Polyimide
- Insulated grade (oC) :UL H/200°C
- Temperature range: -73~260

Part No.	Product No.	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
28302	911-32-50mm	Teflon Adhesive Tape	50mm	0.055	260?




Part No.	Product No.	Manufacturer	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
49100	973UL-0.13mm/19mm/10M		NITOFLOX Tape	19*10	0.13mm	-60*180
39567	973UL-13mm/10M	NITTO DENKO	NITOFLOX Tape	13*10	0.13	-60*180
39570	973UL-19mm/25M	NITTO DENKO	NITOFLOX Tape	19*25	0.13mm	-60*180
39571	973UL-19mm/38M	NITTO DENKO	NITOFLOX Tape	19*38	0.13mm	-60*180
39576	973UL-19mm/50M	NITTO DENKO	NITOFLOX Tape	19*50	0.13mm	-60*180
40601	973UL-S-100mm/10M	NITTO DENKO	NITOFLOX Tape	100mm*10M	0.13mm	-60*180
39564	973UL-S-19mm/10M	NITTO DENKO	NITOFLOX Tape	19*10	0.13mm	-60*180



Part No.	Product No.	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
23515	KA00 12	Teflon Adhesive Tape	12mm	0.055mm	260 °C
23586	KA00 15	Teflon Adhesive Tape	15mm	0.055	260 °C
49800	KA00 20	Teflon Adhesive Tape	20mm	0.055	260 °C
49799	KA00 25-260	Teflon Adhesive Tape	25mm	0.055	260 °C
51797	KA00 25-300	Teflon Adhesive Tape	25mm	0.055	300 °C
23489	KA00 6	Teflon Adhesive Tape	6mm	0.055	260 °C
27081	KA00 8	Teflon Adhesive Tape	8mm	0.055	260 °C
27080	KA00-10	Teflon Adhesive Tape	10mm	0.055	260 °C



Part No.	Product No.	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
17439	KX-06*33	Tape For PC Board	20*33M	0.058mm	180 °C
16463	KX-20*33	Tape For PC Board 180	20*33M	0.058mm	180 °C
16464	KX-25*33	Tape For PC Board	25*33M	0.058mm	180 °C



FEATURES

- UL510 certified.
- Environment-friendly and complies with Notification No.20 of the Ministry of Health, Labor and Welfare.
- Superior in mold-releasing and sliding property.
- Uses the Class H insulating material.
- Superior flame resistance.
- Non-adhesive side of the tape offers excellent characteristics of polytetrafluoroethylene, such as electrical property, resistance to heat, weather, chemical, and water (water-shedding), low friction coefficient and non-adhesiveness.
- Can smoothly adhere, wind, band and seal, just like regular adhesive tapes.

Part No.	Product No.	Manufacturer	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
47435	NO.903UL-75mm/10M	NITTO DENKO	P.T.F.E Resin Product NITOFLOX Adhesive Tape	75*10	0.08mm	-60*180



Part No.	Product No.	Manufacturer	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
12816	T00690250		3M_Glass Cloth Electrical Tape	25mm*30M	0.18mm	180 °C
5949	T06930200	3M	3M_Glass Cloth Electrical Tape	20mm*30M	0.18mm	180 °C
14672	T06930350	3M	3M_Glass Cloth Electrical Tape	35mm*30M	0.18mm	180 °C



Part No.	Product No.	Manufacturer	Description	Size W(mm)*L(M)	Thickness(mm)	Temp.(° C)
12469	T13500250W	3M	3M_Heatproof Tape	25mm*66M	0.06mm	130 °C
5958	T13500500B	3M	3M_Heatproof Tape 130	50mm*66M	0.06mm	130 °C
10127	T13500500BL	3M	3M_Heatproof Tape	50mm*66M	0.06mm	130 °C
7980	T13500500G	3M	3M_Heatproof Tapes 130	50mm*66M	0.06mm	130 °C
5959	T13500500R	3M	3M_Heatproof Tape 130	50mm*66M	0.06mm	130 °C
12468	T13500500W		3M_Heatproof Tape 130	50mm*66M	0.06mm	130 °C
2595	T13500500Y	3M	3M_Heatproof Tapes 130	50mm*66M	0.06mm	130 °C

