

Adhesives & Cleaning & Service AIDS

Protective Coatings

Detailed product specifications are available on: us.100y.com.tw



- DCA is suitable both for use in manual spray guns and computer controlled airless spray equipment that only coats the required areas of the PCB, eliminating the need for masking.
- The nozzle of the spray gun requires to be selected to give an even spray to suit the prevailing viscosity of the coating material. The normal spray gun pressure required is $27.6 \times 10^6 \text{ kN/m}^2$ to $34.5 \times 10^6 \text{ kN/m}^2$ (40 - 50 lbs/sq.inch)
- To ensure penetration of the coating beneath the components and in confined spaces, spray the assembly from all directions to give an even coating.
- After spraying, the boards should be placed in an air-circulating drying cabinet and left to dry for 2 hours at room temperature prior to any heat curing.

Part No.	Product No.	Manufacturer	Description	Capacity
13628	DCA200H	ELECTROLUB	Silicone Resin Conformal Coating	200ml



FEATURES

- An excellent electrical contact lubricant, electrical contact setting, and smooth mechanical setting selection and performance.
- Reduces contact resistance to a low stable level without altering frequency through the components designed variable setting range.
- Non-silicone, synthetic lubricant, eliminating problems caused by carbon deposits and silicone migration.
- Clear, non-staining, anti-static.
- Conveniently packed in aerosol with extension tube for inaccessible areas.
- Compatible with most plastics, paints and rubbers.
- Prevents capacitance, resistance and frequency deviations, erratic high and low setting spots, sparking and tracking.
- Rapid solvent evaporation ensures swift return to normal operation.

Part No.	Product No.	Manufacturer	Description	Capacity
31504	EML-05P	ELECTROLUB	Electronic Cleaning Solvent Plus	5ml



Part No.	Product No.	Manufacturer	Description	Capacity
50687	IS-72	KONTAKT	Protective Coatings	200ml/Can



Part No.	Product No.	Manufacturer	Description	Capacity
50688	PS-70-200ml	KONTAKT	Insulated Protective	200ml/Can
50689	PS-70-400ml	KONTAKT	Insulated Protective	400ml/Can

Label Remover Label & Adhesive Remover

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Manufacturer	Description	Capacity	Color
5530	ES8051	Chemtronics	Chemtronics_Label Remover	200ml	White
14261	K-50	KONTAKT	KONTAKT_LABEL OFF 50 Label Remover	200ml	Limpid

PCB Adhesives PCB Adhesives

Detailed product specifications are available on: us.100y.com.tw



General information

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the material safety data sheet (MSDS)

Part No.	Product No.	Manufacturer	Description	Capacity
17453	L315-75+L188-61	LOCTITE	Thermally Conductive+Self Shimming	315->300mil Speedly->1.75oz

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170

Shanghai: 021-54151736 Shenzhen: 0755-83298787

Centenary Materials

Waiting for your phone call



T E L : Taiwan: 886-3-5753170
F A X : Taiwan: 886-3-5753172
E-mail: Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
Shenzhen: 86-755-83640655
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
Shanghai: 86-21-64605107
Shanghai: 100y-1@163.com