

# Lubricants & Greases

## Lubricants De-Moisturising Fluid/Lubricant

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)



### General Information

TKX is an all-purpose penetrant, lubricant and protectant which will displace moisture, loosen frozen parts and protect against corrosion. TKX is an excellent lubricant for cables, gears, and chains. TKX provides a nondrying, oily film for lubricating equipment and machines. TKX has a high flash point of 175°F, so it can be used in areas where flammability may be a potential problem. TKX doesn't contain chlorinated solvents or silicones, and it is safe to use on most surfaces.

Part No.	Product No.	Manufacturer	Description	Capacity
40053	02016	LPS	LPS TKX All-Purpose Penetrant, Lubricant and Protectant	11 oz. (400ML)



### FEATURES

- Displaces water, moisture and damp from all surfaces because of its acute angle of contact against the relatively high angle presented by water, its very low surface tension and high capillary action drives water away from the surfaces and fills the pores as the water disperses.
- Stops rust and corrosion by ensuring that water and moisture cannot penetrate where rust and corrosion originate. For long term protection, if items are to be stored in aggressive environments, Permagard 40 should be applied at regular intervals as part of a maintenance schedule.
- Penetrates seized parts and enables them to be freed more easily, thereby preventing damage due to excessive forces that would have to be used if it was not applied, as well as the time that can be saved.
- Good lubricant - its deep penetration reduces coefficient of friction between surfaces and it can be used with confidence on small diameter load bearing surfaces in inaccessible locations. For heavy duty bearings which have seized, Permagard 40 can be used to release them prior to being re-greased or oiled with the suitable Electrolube mechanical lubricant.
- Stops electrical leakage by removing damp and moisture which provide leakage paths for current flow.

Part No.	Product No.	Manufacturer	Description	Capacity
2528	EPE200H	ELECTROLUB	Rust-proof Oil	200ml/Bottle



G-2000



K-40



K-85

Part No.	Product No.	Manufacturer	Description	Capacity
50680	G-2000	KONTAKT	Protection and lubrication of plated connectors and contacts	200ml/Can
50678	K-40	KONTAKT	LUBRICANTS	200ml/Can
50677	K-85	KONTAKT	PTFE antifriction	200ml/Can



- All purpose lubricant which forms a unique air tight coating that simultaneously dries as it protects, unlike other lubricants which stay "wet" and attract dirt.
- Lubricates parts, prevents rust, cleans, stops squeaks, displaces moisture, and is non conductive.

Part No.	Product No.	Manufacturer	Description	Capacity	Weight
52042	M1-400ml	Starrett	M1-All Purpose lubricant	400ml	380g/can



Nx129



Nx20



Nx31

Part No.	Product No.	Description	Capacity
49734	NX129	Green mold KOHZAI_NX129 Antirust	480ML
49732	NX20	Long-term lubricants KOHZAI_NX20	300ML
49720	NX31	KOHZAI_NX31 antirust oil	300ML



S-88

Part No.	Product No.	Manufacturer	Description	Capacity
50679	S-88	KONTAKT	High Quality antifriction	200ml/Can



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: [100y-1@163.com](mailto:100y-1@163.com)