

Hand Tools & Kits

Standard Cable Stripper

Detailed product specifications are available on: us.100y.com.tw



Part No.	Product No.	Manufacturer	Description	For cable No.	φ Dia.
43479	8PK-342	Pro'sKit	Cable Stripper	0.010"-0.0125"	2.8, 5, 8MM



HT-322 with streamlined design, no replacement cassette is needed and no adjustment for V-Block, Tool has been preset for RG58/59/6.

For stripping different materials of cable, use the built-in hex key to align the sensitive socket and adjust the blade for good results

Part No.	Product No.	Description	For cable No.
43488	HT-312A	Cable Stripper	RG-59/62/6/4C/5C



Strip cables from 4.5-25mm (18"-10") diameter

Part No.	Product No.	Description	For cable No.
43487	HT-325	Cable Stripper	4.5MM-25MM



Body made of ABS Cutter made of SK-5 Stripper for glass fiber optic φ 0.254mm(0.010") & 0.32mm(0.0125")

Part No.	Product No.	Manufacturer	Description	For cable No.
9936	HT-342	HANLONG	Cable Stripper	0.254mm(0.010 ") & 0.32mm(0.0125 ")



Specification:

- Function: Fiber Optic stripper
- Length : 6.38" (162±3mm)
- Weight : 118g
- Material : Middle Carbon Steel And Harden.
- Frame : Black Oxide Finished.
- Handle : TPR Black (#426c) & TPR Yellow(#136c)

Part No.	Product No.	Description	Length
50807	HT-S144H	Fiber Optic Stripper	162mm



For Stripping Round Cable, Stranded Wire, Multi-Conductor Cable, and Irregular out shape cable from 22AWG up to φ9.5mm(3/8")

Instructions

1. Flat Wire Stripper, by inserting cable between the stripper blades. Squeeze handles, cable must be keep perpendicular and then pull from the tool. Available for following cables:

- Stranded phone wire 2P,4P,6P,10P,etc.
- Intercom/Alarm wire/2-Cond. Speaker wire
- 18-22AWG and SPT-1 Electric wire

2. Round Cable Stripper, by rotating 1-3 times at counterclockwise, and then open the jaw and remove the outer jacket.

Available for following cables:

- Round Cable : Tough insulation 12-14-16 AWG cable, SPT-2 electric wire.
- Assorted solid modular wire : UTP, STP, Data Communication wire and Network cable.
- Multi-Conductor cable : Insulation O.D. 3.2mm to 9.5mm (1/8"-3/8")
- Automotive/Heavy-duty wire max. 8 AWG.

3. Adjusting Bolt control for different cable sizes.

Part No.	Product No.	Manufacturer	Description	For cable No.
11203	HT-S501A	HANLONG	Cable Stripper	9.5mm(3/8 ")



Part No.	Product No.	Description	For cable No.
15504	K131-01	Coaxial Cable Stripper	RG11



ROTARY CABLE STRIPPER FOR CABLE OUT DIAMETER FROM 14mm² UP TO 250mm²

Part No.	Product No.	Description	For cable No.	Length
51447	LY-2047	ROTARY CABLE STRIPPER FOR CABLE	№14mm ² -250mm ²	137mm

