

Power Tools & Drill Bits & Abrasives

PROXXON Power Drills

Detailed product specifications are available on: us.100y.com.tw



The table fits all mill/drill units with 20mm collars. The 300 x 180mm table is die-cast in aluminium and supplied with an adjustable, double section fence. The transparent guard prevents accidental contact with the cutter and the mitre gauge slides in a machined slot. The drive unit is fitted under the table in the 20mm collar adapter. Depth of cut is adjustable by means of a knob and the cutter/drive may be tilted through 45°. This facilitates additional profiles without having to purchase numerous cutters. The complete table is secured to the worktop by means of 4 screws. When using the unit occasionally, a plate and 2 clamps should suffice.

Part No.	Product No.	Manufacturer	Description	Weight
47204	28050	PROXXON	PROXXON_Router table FT 300	1.89KG



Technical Data:

220 - 240V motor with spindle speeds 1,080, 3,100 and 6,400rpm. Quill travel 63mm, headstock travel via the crank 70mm. Throat of 140mm. Maximum drill bit size 10mm, which is also the capability in steel. The optional collets offer a capability to 6mm. Useable table size 200 x 200mm. Column 45 x 500mm.

Part No.	Product No.	Manufacturer	Description	Voltage	Weight
39733	28124	PROXXON	PROXXON_Bench Drill Press TBH	220V	10.7KG



Machined worktop of high quality, ribbed die-cast aluminium (220 x 120mm). Adjustable fence with scale. Solid, hard-chromed steel column, 280mm high, 20mm diameter. Super stable die-cast head with VDE approved 220-240V, 85W motor. Very quiet and of long life expectancy type. Power transmission by aluminium pulleys and flat belt. Three spindle speeds of 1,800, 4,700 and 8,500rpm. (Triple torque at low speeds). Chrome feed lever with adjustable depth scale. The spindle is essentially play-free as a result of the 3 high quality ball bearings. Recessed spindle for insertion of MICROMOT steel collets, but also threaded for drill chucks (3/8" thread).

Part No.	Product No.	Manufacturer	Description	Voltage	Weight
46716	28128-230V	PROXXON	PROXXON_Bench drill machine	230V	3.8KG



Die-cast zinc with three machined sides. The slot fits the adjustable fence of the drill stand MB 140/S and bench drill TBM 220.

Horizontal and vertical V-slots in jaw. Jaw width 50mm and height 10mm. Maximum clamping width 34mm.

Part No.	Product No.	Manufacturer	Description	Spec.	Weight
51198	28132	PROXXON	PROXXON_Machine Vise MS 4	Jaw w:50mm/ h:10mm/Maximum clamping w:34mm	0.6Kg



Technical Data:

220-240V, 50-60Hz, maximum power consumption of 100W. Speed approx. 0-3,000rpm. Chuck capacity 0.5-6mm. Capacity in mild steel 5mm. Weighs 500g and isolated to class 2.

Part No.	Product No.	Manufacturer	Description	Voltage	Weight
47111	28490-230V	PROXXON	PROXXON_Pocket drilling machine Colt 220/E	230V	500G




As 50/E, except that no speed control is fitted. No load speed is 20,000 rpm.

Part No.	Product No.	Manufacturer	Description	Voltage	Spec.
46870	28500	PROXXON	PROXXON_Precision milling/drilling machine MICROMOT 50	110Vac/12DC Adapter	20000rpm



As detailed above, but without clamp. A strong suction cup facilitates instantaneous fixing to any smooth, flat surface.

Part No.	Product No.	Manufacturer	Description
47188	28602	PROXXON	PROXXON_Precision vise FMS 75



The 120 x 220mm table is milled and fitted with a fence and scale. The solid column is chrome plated. The headstock is of die-cast aluminium, offering a throat capacity of 140mm and 30mm travel. A chromed feed lever operates via drive disc and ball bearing system, offering a sensitive feed set-up. T-bars allow simple height adjustment as well as the fixing of the mill drill in the 20mm bore fitting.

Part No.	Product No.	Manufacturer	Description	Spec.	Weight
14885	28606	PROXXON	PROXXON_Drill Stand MB 140/S	table:220*120mm	2.1 Kg

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170

Shanghai: 021-54151736 Shenzhen: 0755-83298787

Centenary Materials
Waiting for your phone call



T E L : Taiwan: 886-3-5753170
F A X : Taiwan: 886-3-5753172
E-mail: Taiwan: us_sale@100y.com.tw

Shenzhen: 86-755-83298787
Shenzhen: 86-755-83640655
Shenzhen: 100y@163.com

Shanghai: 86-21-54151736
Shanghai: 86-21-64605107
Shanghai: 100y-1@163.com