

# New Products

## Other Type New Products

Detailed product specifications are available on: [us.100y.com.tw](http://us.100y.com.tw)

Part No.	Product No.	Description
41227	FV-28	All-In-One Stamp-Sized GPS Module



Part No.	Product No.	Description	Other #2
50445	G65SC22P-2	CMOS Versatile Interface Adapter With Interval Timer/Counters	DIP/40P



### Features

- InGaP HBT microwave amplifiers
- miniature SOT-89 package
- frequency range, DC to 8 GHz, usable to 10 Ghz
- up to 18.2 dBm typ. output power
- excellent package for heat dissipation, exposed metal bottom
- low thermal resistance for high reliability
- protected by US Patent, 6,943,629

Part No.	Product No.	Manufacturer	Description	Other #2	Other #3
37799	GALI-5+	Mini-Circuits	Surface Mount MONOLITHIC AMPLIFIERS (RoHS)	DC to 8 GHz	50Ω
37800	GALI-52+	Mini-Circuits	Surface Mount MONOLITHIC AMPLIFIERS(RoHS)	DC to 8 GHz	50Ω




Part No.	Product No.	Description	Other #2	Other #3
49523	GARMIN-nuvi360	GARMIN-nuvi360	1GB	3.5" SCREEN



- Symmetrical TX and RX channels for Auto MDI/MDIX capability
- Approved for use with the Broadcom BCM5226 and Level One LXT9784
- Compliant with IEEE 802.3u and ANSI X3.263 standards including 350 μH OCL with 8 mA bias
- Designed for reflow soldering at temperatures up to 235°C


Part No.	Product No.	Manufacturer	Description
27118	H1164	Pulse	10/100BASE-TX TRANSFORMER MODULES For Auto MDI/MDIX Applications



### Features

- Guaranteed 20 mA Loop Parameters
- Data Input Compatible with LSTTL, TTL and CMOS Logic
- Guaranteed Performance over Temperature (0°C to 70°C)
- Internal Shield for High Common Mode Rejection
- 20 kBaud Data Rate at 400 Metres Line Length
- Guaranteed On and Off Output Current Levels
- Safety Approval UL Recognized -3750 V rms for 1 minute CSA Approved
- Optically Coupled 20 mA Current Loop Receiver, HCPL-4200, Also Available

Part No.	Product No.	Manufacturer	Description	Other #2
33294	HCPL-4100	Agilent	Optically Coupled 20 mA Current Loop Transmitter	8-Pin DIP



### Features

- Data Output Compatible with LSTTL, TTL and CMOS
- 20 K Baud Data Rate at 1400 Metres Line Length
- Guaranteed Performance over Temperature (0°C to 70°C)
- Guaranteed On and Off Thresholds
- LED is Protected from Excess Current
- Input Threshold Hysteresis
- Three-State Output Compatible with Data Buses
- Internal Shield for High Common Mode Rejection
- Safety Approval UL Recognized -3750 V rms, for 1 Minute CSA Approved
- Optically Coupled 20 mA Current Loop Transmitter, HCPL-4100, Also Available

Part No.	Product No.	Manufacturer	Description	Other #2
33308	HCPL-4200	Agilent	Optically Coupled 20 mA Current Loop Receiver	8 Pin DIP

- We provide a wide range of products to development and maintenance engineers in all type of business
- If you cannot find the components you want on the catalogue, please call us.



Taiwan: 886-3-5753170  
Shanghai: 021-54151736 Shenzhen: 0755-83298787

**Centenary Materials**  
Waiting for your phone call



T E L : Taiwan: 886-3-5753170  
F A X : Taiwan: 886-3-5753172  
E-mail: Taiwan: [us\\_sale@100y.com.tw](mailto:us_sale@100y.com.tw)

Shenzhen: 86-755-83298787  
Shenzhen: 86-755-83640655  
Shenzhen: [100y@163.com](mailto:100y@163.com)

Shanghai: 86-21-54151736  
Shanghai: 86-21-64605107  
Shanghai: [100y-1@163.com](mailto:100y-1@163.com)